PROFESSIONAL LIGHTING

LE480604230

LED PLT GX24q-4 4 pin Glass T45x167mm
20W 1980Lm 830 3000K (repl. PLTE42W)
Opal ECG Non-Dimmable

Marine & Industry, PLT GX24q 4pin ECG

General	
Eprel registration no	2757660
Socket	GX24q-4
Bulb shape	T45
Width	45.00 mm
Depth	49.50 mm
Height	167.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	360 °
Dimmable	No
Degree of protection	IP20
Net weight	0.097 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	20 W
Current type	AC
Power factor	0.7
Energy efficiency class	F
Energy consumption	20 W
Lamp efficacy	99.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	108
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	1980 lm

Ordering details		
LE480604230	Quantity pc(s)	EAN
Single package	1	8718739075672
Inner carton	10	18718739075679
Outer carton	50	28718739075676

Remark

For easy replacement of conventional PL lamps in existing luminaires with a compatible electronic control gear. Plug-and-play installation without any wiring modifications.

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal