



PROFESSIONAL  
LIGHTING

LF023820312

LED E27 Filament Ball G45x75mm 230V  
370Lm 4W 2500K 925 360° AC Clear  
Dimmablea

Decorative, Ball E27 Premium



General		Energy																			
Epel registration no	1196473	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	4 W																		
Depth	45.00 mm	Current type	AC																		
Height	75.00 mm	Power factor	0.9																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	33 W																		
Lifespan	25000 hours	Lamp efficacy	92.50																		
Switches	15000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.010 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LF023820312</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739066885</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739066882</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739066889</td></tr></table>		LF023820312	Quantity pc(s)	EAN	Single package	1	8718739066885	Inner carton	10	18718739066882	Outer carton	100	28718739066889						
LF023820312	Quantity pc(s)			EAN																	
Single package	1			8718739066885																	
Inner carton	10			18718739066882																	
Outer carton	100			28718739066889																	
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	370 lm																				
Color Rendering Index (CRI)	90																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

22-12-2024