



PROFESSIONAL  
LIGHTING

## LF023851502

LED E14 Filament Tip Candle C35x120mm  
230V 140Lm 1.5W 2500K 925 360° AC Clear  
Dimmable

### Decorative, Tip Candle Premium



General		Energy																			
Epel registration no	658527	Operating voltage	230 V																		
Socket	E14	Volt	220..240 V																		
Bulb shape	C35	Frequency	50..60 Hz																		
Width	35.00 mm	Watt	1.5 W																		
Depth	35.00 mm	Current type	AC																		
Height	120.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	2 W																		
Body material	Glass	Replacement wattage	15 W																		
Lifespan	25000 hours	Lamp efficacy	93.33																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Twisted</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	2	Stick length	38 mm	Stick mounting	Twisted	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	2																				
Stick length	38 mm																				
Stick mounting	Twisted																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.015 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LF023851502</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739055025</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739055022</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739055029</td></tr></table>		LF023851502	Quantity pc(s)	EAN	Single package	1	8718739055025	Inner carton	10	18718739055022	Outer carton	100	28718739055029						
LF023851502	Quantity pc(s)			EAN																	
Single package	1			8718739055025																	
Inner carton	10			18718739055022																	
Outer carton	100			28718739055029																	
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	140 lm																				
Color Rendering Index (CRI)	93																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

26-06-2025