



PROFESSIONAL
LIGHTING

LF023863092

LED E27 Filament R63x103mm 230V 320Lm
5.5W 2500K 925 120° AC Clear Dimmable

Decorative, Reflector Fila Premium



| General | | Energy | | | | | | | | | | | | | | | | | | | |
|-----------------------------|-----------------------------------|---|------------|----------------|----------------|----------|----------------|-----------|---------------------------|-------------------------|----|----------------|--------------|----------------|-----------------------------------|-------------------------|-------|-------------|----|-----------------------|----|
| Epel registration no | 831777 | Operating voltage | 230 V | | | | | | | | | | | | | | | | | | |
| Socket | E27 | Volt | 220..240 V | | | | | | | | | | | | | | | | | | |
| Bulb shape | R63 | Frequency | 50..60 Hz | | | | | | | | | | | | | | | | | | |
| Width | 63.00 mm | Watt | 5.5 W | | | | | | | | | | | | | | | | | | |
| Depth | 63.00 mm | Current type | AC | | | | | | | | | | | | | | | | | | |
| Height | 103.00 mm | Power factor | 0.9 | | | | | | | | | | | | | | | | | | |
| Finish | Clear | Energy efficiency class | G | | | | | | | | | | | | | | | | | | |
| Colour | Silver | Energy consumption | 6 W | | | | | | | | | | | | | | | | | | |
| Body material | Glass | Lamp efficacy | 58.18 | | | | | | | | | | | | | | | | | | |
| Lifespan | 25000 hours | <div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>6</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight - Top narrow bottom wide</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> | | Filament LED | Yes | LED type | Ceramic | Dimm type | Trailing and leading edge | Number of leds / sticks | 6 | Stick length | 38 mm | Stick mounting | Straight - Top narrow bottom wide | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED | Yes | | | | | | | | | | | | | | | | | | | | |
| LED type | Ceramic | | | | | | | | | | | | | | | | | | | | |
| Dimm type | Trailing and leading edge | | | | | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 6 | | | | | | | | | | | | | | | | | | | | |
| Stick length | 38 mm | | | | | | | | | | | | | | | | | | | | |
| Stick mounting | Straight - Top narrow bottom wide | | | | | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM6 | | | | | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | | | | | |
| Switches | 50000 | | | | | | | | | | | | | | | | | | | | |
| Beam angle | 120 ° | | | | | | | | | | | | | | | | | | | | |
| Dimmable | Yes | | | | | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | | | | | |
| Net weight | 0.035 kg | | | | | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | | | | | |
| Light | | <div>Ordering details</div> <table><tr><td>LF023863092</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739056466</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739056463</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739056460</td></tr></table> | | LF023863092 | Quantity pc(s) | EAN | Single package | 1 | 8718739056466 | Inner carton | 10 | 18718739056463 | Outer carton | 100 | 28718739056460 | | | | | | |
| LF023863092 | Quantity pc(s) | | | EAN | | | | | | | | | | | | | | | | | |
| Single package | 1 | | | 8718739056466 | | | | | | | | | | | | | | | | | |
| Inner carton | 10 | | | 18718739056463 | | | | | | | | | | | | | | | | | |
| Outer carton | 100 | | | 28718739056460 | | | | | | | | | | | | | | | | | |
| Kelvin | 2500 K | | | | | | | | | | | | | | | | | | | | |
| Colour temp nr | 925 | | | | | | | | | | | | | | | | | | | | |
| Stable lumen | 320 lm | | | | | | | | | | | | | | | | | | | | |
| Lumen 120 cone | 300 lm | | | | | | | | | | | | | | | | | | | | |
| Luminous intensity | 190 cd | | | | | | | | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 93 | | | | | | | | | | | | | | | | | | | | |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

01-05-2024