




PROFESSIONAL  
LIGHTING

LF023899905

LED E27 Filament XXL GLS Spiral  
A165x300mm 230V 450Lm 6W 2200K 922  
360° AC Gold Dimmable

Decorative, Big Globe Premium



General		Energy																			
Epel registration no	831812	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	A165	Frequency	50..60 Hz																		
Width	165.00 mm	Watt	6 W																		
Depth	165.00 mm	Current type	AC																		
Height	300.00 mm	Power factor	0.85																		
Finish	Clear	Energy consumption	6 W																		
Colour	Gold	Replacement wattage	39 W																		
Body material	Glass	Lamp efficacy	75.00																		
Lifespan	25000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>12</td></tr><tr><td>Stick length</td><td>28 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Axial</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	12	Stick length	28 mm	Stick mounting	Spiral Axial	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	12																				
Stick length	28 mm																				
Stick mounting	Spiral Axial																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.367 kg																				
Warranty	2 years																				
<div>Light</div> <table><tr><td>Kelvin</td><td>2200 K</td></tr><tr><td>Colour temp nr</td><td>922</td></tr><tr><td>Stable lumen</td><td>450 lm</td></tr><tr><td>Color Rendering Index (CRI)</td><td>90</td></tr></table>		Kelvin	2200 K	Colour temp nr	922	Stable lumen	450 lm	Color Rendering Index (CRI)	90												
Kelvin	2200 K																				
Colour temp nr	922																				
Stable lumen	450 lm																				
Color Rendering Index (CRI)	90																				
<div>Ordering details</div> <table><tr><td>LF023899905</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739052543</td></tr><tr><td>Outer carton</td><td>4</td><td>28718739052547</td></tr></table>				LF023899905	Quantity pc(s)	EAN	Single package	1	8718739052543	Outer carton	4	28718739052547									
LF023899905	Quantity pc(s)	EAN																			
Single package	1	8718739052543																			
Outer carton	4	28718739052547																			



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)



18-05-2025