



PROFESSIONAL  
LIGHTING

## LF023925005

LED E27 Filament Flex TR Globe  
G125x180mm 230V 140Lm 4W 360° AC  
Yellow Dimmable

**Decorative, Flex Globe Coloured  
Premium**



| General                     |                | Energy                  |                           |
|-----------------------------|----------------|-------------------------|---------------------------|
| Epel registration no        | 600736         | Operating voltage       | 230 V                     |
| Socket                      | E27            | Volt                    | 220..240 V                |
| Bulb shape                  | G125           | Frequency               | 50..60 Hz                 |
| Width                       | 125.00 mm      | Watt                    | 4 W                       |
| Depth                       | 125.00 mm      | Current type            | AC                        |
| Height                      | 180.00 mm      | Power factor            | 0.85                      |
| Finish                      | Clear          | Energy consumption      | 4 W                       |
| Colour                      | Yellow         | Replacement wattage     | 15 W                      |
| Body material               | Glass          | Lamp efficacy           | 35.00                     |
| Lifespan                    | 15000 hours    | <b>LED</b>              |                           |
| Switches                    | 30000          | Filament LED            | Yes                       |
| Beam angle                  | 360 °          | LED type                | Flex                      |
| Dimmable                    | Yes            | Dimm type               | Trailing and leading edge |
| Degree of protection        | IP20           | Number of leds / sticks | 1                         |
| Net weight                  | 0.096 kg       | Stick length            | 300 mm                    |
| Warranty                    | 2 years        | Stick mounting          | Spiral Transversal        |
| <b>Light</b>                |                | Colour consistency SDCM | SDCM6                     |
| Stable lumen                | 140 lm         | Dim to warm             | No                        |
| Color Rendering Index (CRI) | 93             | Adjustable beam angle   | No                        |
| <b>Ordering details</b>     |                |                         |                           |
| LF023925005                 | Quantity pc(s) | EAN                     |                           |
| Single package              | 1              | 8718739063952           |                           |
| Outer carton                | 12             | 28718739063956          |                           |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)



07-06-2025