



PROFESSIONAL
LIGHTING

LF024040302

LED Ba15d Filament Candle C35x100mm
230V 320Lm 4W 2500K 925 360° AC Clear
Dimmable

Decorative, Candle Premium



General		Energy																			
Eprel registration no	831893	Operating voltage	230 V																		
Socket	Ba15d	Volt	220..240 V																		
Bulb shape	C35	Frequency	50..60 Hz																		
Width	35.00 mm	Watt	4 W																		
Depth	35.00 mm	Current type	AC																		
Height	100.00 mm	Power factor	0.9																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	30 W																		
Lifespan	25000 hours	Lamp efficacy	80.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Twisted</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Twisted	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Twisted																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.016 kg																				
Warranty	2 years																				
Light		Ordering details																			
Kelvin	2500 K	LF024040302	Quantity pc(s)	EAN																	
Colour temp nr	925	Single package	1	8718739058187																	
Stable lumen	320 lm	Inner carton	10	18718739058184																	
Color Rendering Index (CRI)	93	Outer carton	100	28718739058181																	



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)