



LF229505622

LED Ba22d Filament Tube T30x95mm 230V
470Lm 5W 2700K 827 360° AC Clear
Dimmable

Marine & Industry, Tubular Filament



General		Energy																			
Eprel registration no	545634	Operating voltage	230 V																		
Socket	Ba22d	Volt	220..240 V																		
Bulb shape	T30	Frequency	50..60 Hz																		
Width	30.00 mm	Watt	5 W																		
Depth	30.00 mm	Current type	AC																		
Height	95.00 mm	Power factor	0.9																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	5 W																		
Body material	Glass	Replacement wattage	40 W																		
Lifespan	25000 hours	Lamp efficacy	94.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>6</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight - Top narrow bottom wide</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	6	Stick length	38 mm	Stick mounting	Straight - Top narrow bottom wide	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	6																				
Stick length	38 mm																				
Stick mounting	Straight - Top narrow bottom wide																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.026 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LF229505622</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739054660</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739054667</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739054664</td></tr></table>		LF229505622	Quantity pc(s)	EAN	Single package	1	8718739054660	Inner carton	10	18718739054667	Outer carton	100	28718739054664						
LF229505622	Quantity pc(s)			EAN																	
Single package	1			8718739054660																	
Inner carton	10			18718739054667																	
Outer carton	100	28718739054664																			
Kelvin	2700 K																				
Colour temp nr	827																				
Stable lumen	470 lm																				
Color Rendering Index (CRI)	80																				

