



PROFESSIONAL  
LIGHTING

## LS147230022

LED E14 Slim Flex Filament Ball G45x80  
mm 230V 320Lm 3.2W 2200K 922 360° AC  
Clear Dimmable

## Decorative, Flex Slim Premium



| General                     |             | Energy                  |                |
|-----------------------------|-------------|-------------------------|----------------|
| Epel registration no        | 1471266     | Operating voltage       | 230 V          |
| Socket                      | E14         | Volt                    | 220..240 V     |
| Bulb shape                  | G45         | Frequency               | 50..60 Hz      |
| Width                       | 45.00 mm    | Watt                    | 3.2 W          |
| Depth                       | 45.00 mm    | Current type            | AC             |
| Height                      | 80.00 mm    | Power factor            | 0.5            |
| Finish                      | Clear       | Energy efficiency class | F              |
| Colour                      | Colourless  | Energy consumption      | 3 W            |
| Body material               | Glass       | Replacement wattage     | 30 W           |
| Lifespan                    | 15000 hours | Lamp efficacy           | 100.00         |
| Switches                    | 20000       | LED                     |                |
| Beam angle                  | 360 °       | Filament LED            | Yes            |
| Dimmable                    | Yes         | LED type                | Flex           |
| Degree of protection        | IP20        | Dimm type               | Non-Dim        |
| Net weight                  | 0.015 kg    | Number of leds / sticks | 1              |
| Warranty                    | 2 years     | Stick length            | 116 mm         |
| Light                       |             | Stick mounting          | Spiral         |
| Kelvin                      | 2200 K      | Colour consistency SDCM | SDCM6          |
| Colour temp nr              | 922         | Dim to warm             | No             |
| Stable lumen                | 320 lm      | Adjustable beam angle   | No             |
| Color Rendering Index (CRI) | 90          | Ordering details        |                |
|                             |             | LS147230022             | Quantity pc(s) |
|                             |             | Single package          | 1              |
|                             |             | Inner carton            | 10             |
|                             |             | Outer carton            | 100            |
|                             |             | EAN                     |                |
|                             |             | 8718739069480           |                |
|                             |             | 18718739069487          |                |
|                             |             | 28718739069484          |                |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

29-06-2025