



PROFESSIONAL
LIGHTING

LS149300022

LED E14 Slim Flex Filament Candle
C35x98mm 230V 320Lm 3.2W 2200K 922
360° AC Clear Dimmable

Decorative, Flex Slim Premium



| General | | Energy | |
|-----------------------------|-------------|-------------------------|----------------|
| Epel registration no | 1471268 | Operating voltage | 230 V |
| Socket | E14 | Volt | 220..240 V |
| Bulb shape | C35 | Frequency | 50..60 Hz |
| Width | 35.00 mm | Watt | 3.2 W |
| Depth | 35.00 mm | Current type | AC |
| Height | 98.00 mm | Power factor | 0.6 |
| Finish | Clear | Energy efficiency class | F |
| Colour | Colourless | Energy consumption | 3 W |
| Body material | Glass | Replacement wattage | 30 W |
| Lifespan | 15000 hours | Lamp efficacy | 100.00 |
| Switches | 20000 | LED | |
| Beam angle | 360 ° | Filament LED | Yes |
| Dimmable | Yes | LED type | Flex |
| Degree of protection | IP20 | Dimm type | Triac |
| Net weight | 0.014 kg | Number of leds / sticks | 1 |
| Warranty | 2 years | Stick length | 116 mm |
| Light | | Stick mounting | Spiral |
| Kelvin | 2200 K | Colour consistency SDCM | SDCM6 |
| Colour temp nr | 922 | Dim to warm | No |
| Stable lumen | 320 lm | Adjustable beam angle | No |
| Color Rendering Index (CRI) | 90 | Ordering details | |
| | | LS149300022 | Quantity pc(s) |
| | | Single package | 1 |
| | | Inner carton | 10 |
| | | Outer carton | 100 |
| | | EAN | |
| | | 8718739069398 | |
| | | 18718739069395 | |
| | | 28718739069392 | |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

