

LS274525022

LED E27 Slim Flex Filament Tube
T45x110mm 230V 250Lm 2.9W 2200K 922
360° AC Gold Dimmable

Decorative, Flex Slim Premium


General		Energy																			
Eprel registration no	2259469	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	T45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	2.9 W																		
Depth	45.00 mm	Current type	AC																		
Height	110.00 mm	Power factor	0.5																		
Finish	Clear	Energy efficiency class	F																		
Colour	Gold	Energy consumption	3 W																		
Body material	Glass	Replacement wattage	25 W																		
Lifespan	15000 hours	Lamp efficacy	86.21																		
Switches	20000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Triac</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>116 mm</td></tr><tr><td>Stick mounting</td><td>Spiral</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Triac	Number of leds / sticks	1	Stick length	116 mm	Stick mounting	Spiral	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Triac																				
Number of leds / sticks	1																				
Stick length	116 mm																				
Stick mounting	Spiral																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.026 kg																				
Warranty	2 years																				

Light		Ordering details	
Kelvin	2200 K	LS274525022	Quantity pc(s) EAN
Colour temp nr	922	Single package	1 8718739080997
Stable lumen	250 lm	Inner carton	10 18718739080994
Color Rendering Index (CRI)	90	Outer carton	100 28718739080991