

LS276425022

LED E27 Slim Flex Filament Rustika
ST64x140mm 230V 250Lm 2.9W 2200K
922 360° AC Gold Dimmable

Decorative, Flex Slim Premium



General		Energy																			
Eprel registration no	2259465	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	ST64	Frequency	50..60 Hz																		
Width	64.00 mm	Watt	2.9 W																		
Depth	64.00 mm	Current type	AC																		
Height	140.00 mm	Power factor	0.5																		
Finish	Clear	Energy efficiency class	F																		
Colour	Gold	Energy consumption	3 W																		
Body material	Glass	Replacement wattage	25 W																		
Lifespan	15000 hours	Lamp efficacy	86.21																		
Switches	20000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Triac</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>116 mm</td></tr><tr><td>Stick mounting</td><td>Spiral</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Triac	Number of leds / sticks	1	Stick length	116 mm	Stick mounting	Spiral	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Triac																				
Number of leds / sticks	1																				
Stick length	116 mm																				
Stick mounting	Spiral																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.050 kg																				
Warranty	2 years																				
Light		Ordering details																			
Kelvin	2200 K	LS276425022	Quantity pc(s) EAN																		
Colour temp nr	922	Single package	1 8718739080959																		
Stable lumen	250 lm	Inner carton	10 18718739080956																		
Color Rendering Index (CRI)	90	Outer carton	100 28718739080953																		