

LS278047022

LED E27 Slim Flexible Filament Globe
G80x120mm 230V 470Lm 4.2W 2200K 922
360° AC Gold Dimmable

Decorative, Flex Slim Premium



General		Energy																			
Eprel registration no	1790695	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G80	Frequency	50..60 Hz																		
Width	80.00 mm	Watt	4.2 W																		
Depth	80.00 mm	Current type	AC																		
Height	120.00 mm	Power factor	0.5																		
Finish	Clear	Energy efficiency class	E																		
Colour	Gold	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	40 W																		
Lifespan	15000 hours	Lamp efficacy	111.90																		
Switches	20000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Triac</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>152 mm</td></tr><tr><td>Stick mounting</td><td>Spiral</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Triac	Number of leds / sticks	1	Stick length	152 mm	Stick mounting	Spiral	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Triac																				
Number of leds / sticks	1																				
Stick length	152 mm																				
Stick mounting	Spiral																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.040 kg																				
Warranty	2 years																				

Light	
Kelvin	2200 K
Colour temp nr	922
Stable lumen	470 lm
Color Rendering Index (CRI)	90

Ordering details		
LS278047022	Quantity pc(s)	EAN
Single package	1	8718739071605
Outer carton	24	28718739071609