PROFESSIONAL LIGHTING

## LT149125002

LED E14 Filament Candle C35x100mm 230V 250Lm 2.5W 2500K 925 360° AC Clear Dimmable

**Decorative, Candle Premium**

| General | |
|---|---|
| Eprel registration no | 2352867 |
| Socket | E14 |
| Bulb shape | C35 |
| Width | 35.00 mm |
| Depth | 35.00 mm |
| Height | 100.00 mm |
| Finish | Clear |
| Colour | Colourless |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.015 kg |
| Warranty | 2 years |

| Light | |
|---|---|
| Kelvin | 2500 K |
| Colour temp nr | 925 |
| Stable lumen | 250 lm |
| Color Rendering Index (CRI) | 93 |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 2.5 W |
| Current type | AC |
| Power factor | 0.7 |
| Energy efficiency class | F |
| Energy consumption | 3 W |
| Lamp efficacy | 100.00 |

| LED | |
|---|---|
| Filament LED | Yes |
| LED type | Ceramic |
| Dimm type | Triac |
| Number of leds / sticks | 2 |
| Stick length | 38 mm |
| Stick mounting | Vertical |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|---|---|---|
| LT149125002 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739081635 |
| Outer carton | 60 | 28718739081639 |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal