



PROFESSIONAL
LIGHTING

LX023815552

LED E27 Filament Globe G80x120mm 230V
550Lm 6W 2500K 925 360° AC Clear
Dimmable

Decorative, Globe G80 Premium



General		Energy																			
Eprel registration no	1428834	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G80	Frequency	50..60 Hz																		
Width	80.00 mm	Watt	6 W																		
Depth	80.00 mm	Current type	AC																		
Height	120.00 mm	Power factor	0.8																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	6 W																		
Body material	Glass	Replacement wattage	45 W																		
Lifespan	15000 hours	Lamp efficacy	91.67																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Triac</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>52 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Triac	Number of leds / sticks	4	Stick length	52 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM5	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Triac																				
Number of leds / sticks	4																				
Stick length	52 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM5																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.044 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LX023815552</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739068292</td></tr><tr><td>Inner carton</td><td>5</td><td>18718739068299</td></tr><tr><td>Outer carton</td><td>50</td><td>28718739068296</td></tr></table>		LX023815552	Quantity pc(s)	EAN	Single package	1	8718739068292	Inner carton	5	18718739068299	Outer carton	50	28718739068296						
LX023815552	Quantity pc(s)			EAN																	
Single package	1			8718739068292																	
Inner carton	5			18718739068299																	
Outer carton	50			28718739068296																	
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	550 lm																				
Color Rendering Index (CRI)	93																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

