



PROFESSIONAL  
LIGHTING

## LX023820308

LED E27 Filament Ball G45x75mm 230V  
250Lm 4W 2500K 925 360° AC Opal  
Dimmable

## Decorative, Ball E27 Premium



General		Energy																			
Eprel registration no	1441695	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	4 W																		
Depth	45.00 mm	Current type	AC																		
Height	75.00 mm	Power factor	0.85																		
Finish	Opal	Energy efficiency class	G																		
Colour	White	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	25 W																		
Lifespan	25000 hours	Lamp efficacy	62.50																		
Switches	15000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Twisted</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Twisted	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Twisted																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.016 kg																				
Warranty	2 years																				

Light		
Kelvin	2500 K	
Colour temp nr	925	
Stable lumen	250 lm	
Color Rendering Index (CRI)	93	

Ordering details		
LX023820308	Quantity pc(s)	EAN
Single package	1	8718739068933
Inner carton	10	18718739068930
Outer carton	100	28718739068937



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

05-04-2025