



PROFESSIONAL  
LIGHTING

**LX023821509**

LED E27 Filament Ball G45x75mm 230V  
140Lm 2W 2200K 922 360° AC Clear  
Dimmable

**Decorative, Ball E27 Premium**



| General                     |                           | Energy   |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
|-----------------------------|---------------------------|--|-----------------------|--------------|-----|----------|---------|-----------|---------------------------|-------------------------|---|--------------|-------|----------------|----------|-------------------------|-------|-------------|----|-----------------------|----|
| Eprel registration no       | 1988860                   | Operating voltage  | 230 V                 |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Socket                      | E27                       | Volt   | 220..240 V            |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Bulb shape                  | G45                       | Frequency  | 50..60 Hz             |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Width                       | 45.00 mm                  | Watt   | 2 W                   |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Depth                       | 45.00 mm                  | Current type   | AC                    |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Height                      | 75.00 mm                  | Power factor   | 0.9                   |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Finish                      | Clear                     | Energy efficiency class  | G                     |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Colour                      | Colourless                | Energy consumption   | 2 W                   |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Body material               | Glass                     | Replacement wattage  | 15 W                  |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Lifespan                    | 25000 hours               | Lamp efficacy  | 70.00                 |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Switches                    | 50000                     | <div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> |                       | Filament LED | Yes | LED type | Ceramic | Dimm type | Trailing and leading edge | Number of leds / sticks | 2 | Stick length | 38 mm | Stick mounting | Vertical | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED                | Yes                       |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| LED type                    | Ceramic                   |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Dimm type                   | Trailing and leading edge |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Number of leds / sticks     | 2                         |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Stick length                | 38 mm                     |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Stick mounting              | Vertical                  |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Colour consistency SDCM     | SDCM6                     |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Dim to warm                 | No                        |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Adjustable beam angle       | No                        |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Beam angle                  | 360 °                     |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Dimmable                    | Yes                       |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Degree of protection        | IP20                      |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Net weight                  | 0.010 kg                  |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Warranty                    | 2 years                   |  |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Light                       |                           | Ordering details   |                       |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Kelvin                      | 2200 K                    | LX023821509  | Quantity pc(s)<br>EAN |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Colour temp nr              | 922                       | Single package   | 1<br>8718739073319    |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Stable lumen                | 140 lm                    | Inner carton   | 10<br>18718739073316  |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |
| Color Rendering Index (CRI) | 93                        | Outer carton   | 100<br>28718739073313 |              |     |          |         |           |                           |                         |   |              |       |                |          |                         |       |             |    |                       |    |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

09-06-2025