



PROFESSIONAL  
LIGHTING

## LX023840308

LED E14 Filament Candle C35x97mm 230V  
250Lm 3W 2500K 925 360° AC Opal  
Dimmable

### Decorative, Candle Premium



| General                     |             | Energy                  |                           |
|-----------------------------|-------------|-------------------------|---------------------------|
| Epel registration no        | 1318260     | Operating voltage       | 230 V                     |
| Socket                      | E14         | Volt                    | 185..265 V                |
| Bulb shape                  | C35         | Frequency               | 50..60 Hz                 |
| Width                       | 35.00 mm    | Watt                    | 3 W                       |
| Depth                       | 35.00 mm    | Current type            | AC                        |
| Height                      | 97.00 mm    | Power factor            | 0.9                       |
| Finish                      | Opal        | Energy efficiency class | G                         |
| Colour                      | White       | Energy consumption      | 3 W                       |
| Body material               | Glass       | Replacement wattage     | 25 W                      |
| Lifespan                    | 25000 hours | Lamp efficacy           | 83.33                     |
| Switches                    | 30000       | LED                     |                           |
| Beam angle                  | 360 °       | Filament LED            | Yes                       |
| Dimmable                    | Yes         | LED type                | Ceramic                   |
| Degree of protection        | IP20        | Dimm type               | Trailing and leading edge |
| Net weight                  | 0.014 kg    | Number of leds / sticks | 4                         |
| Warranty                    | 2 years     | Stick length            | 38 mm                     |
| Light                       |             | Stick mounting          | Twisted                   |
| Kelvin                      | 2500 K      | Colour consistency SDCM | SDCM6                     |
| Colour temp nr              | 925         | Dim to warm             | No                        |
| Stable lumen                | 250 lm      | Adjustable beam angle   | No                        |
| Color Rendering Index (CRI) | 90          | Ordering details        |                           |
|                             |             | LX023840308             | Quantity pc(s) EAN        |
|                             |             | Single package          | 1 8718739067707           |
|                             |             | Inner carton            | 10 18718739067704         |
|                             |             | Outer carton            | 100 28718739067701        |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

21-11-2024