



PROFESSIONAL
LIGHTING

LX023860609

LED E27 Filament Rustika ST64x143mm
230V 460Lm 5.5W 2200K 922 360° AC
Clear Dimmable

Decorative, Rustika Premium



General		Energy																			
Eprel registration no	1609722	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	ST64	Frequency	50..60 Hz																		
Width	64.00 mm	Watt	5.5 W																		
Depth	64.00 mm	Current type	AC																		
Height	143.00 mm	Power factor	0.89																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	6 W																		
Body material	Glass	Replacement wattage	39 W																		
Lifespan	25000 hours	Lamp efficacy	83.64																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>6</td></tr><tr><td>Stick length</td><td>68 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	6	Stick length	68 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM5	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	6																				
Stick length	68 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM5																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.047 kg																				
Warranty	2 years																				
Light		Ordering details																			
Kelvin	2200 K	LX023860609	Quantity pc(s)																		
Colour temp nr	922	Single package	1																		
Stable lumen	460 lm	Inner carton	10																		
Color Rendering Index (CRI)	90	Outer carton	100																		
			EAN																		
			8718739070677																		
			18718739070674																		
			28718739070671																		



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

26-06-2025