



## LX023861302

LED E27 Filament Candle C35x100mm 230V  
320Lm 4W 2500K 925 360° AC Clear  
Dimmable

## Decorative, Candle Premium



General		Energy																			
Eprel registration no	1594350	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	C35	Frequency	50..60 Hz																		
Width	35.00 mm	Watt	4 W																		
Depth	35.00 mm	Current type	AC																		
Height	100.00 mm	Power factor	0.8																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	30 W																		
Lifespan	25000 hours	Lamp efficacy	80.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.017 kg																				
Warranty	2 years																				
Light		Ordering details																			
Kelvin	2500 K	LX023861302	Quantity pc(s) EAN																		
Colour temp nr	925	Single package	1 8718739069619																		
Stable lumen	320 lm	Inner carton	10 18718739069616																		
Color Rendering Index (CRI)	93	Outer carton	100 28718739069613																		

