



PROFESSIONAL  
LIGHTING

**LX023863092**

LED E27 Filament R63x110mm 230V 400Lm  
5.5W 2500K 925 360° AC Clear Dimmable

**Decorative, Reflector Fila Premium**



General		Energy																			
Eprel registration no	2054938	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	R63	Frequency	50..60 Hz																		
Width	63.00 mm	Watt	5.5 W																		
Depth	63.00 mm	Current type	AC																		
Height	110.00 mm	Power factor	0.9																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	6 W																		
Body material	Glass	Replacement wattage	35 W																		
Lifespan	25000 hours	Lamp efficacy	72.73																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>6</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight - Top narrow bottom wide</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	6	Stick length	38 mm	Stick mounting	Straight - Top narrow bottom wide	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	6																				
Stick length	38 mm																				
Stick mounting	Straight - Top narrow bottom wide																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.035 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LX023863092</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739071100</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739071107</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739071104</td></tr></table>		LX023863092	Quantity pc(s)	EAN	Single package	1	8718739071100	Inner carton	10	18718739071107	Outer carton	100	28718739071104						
LX023863092	Quantity pc(s)			EAN																	
Single package	1			8718739071100																	
Inner carton	10			18718739071107																	
Outer carton	100			28718739071104																	
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	400 lm																				
Color Rendering Index (CRI)	93																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

19-09-2024