



PROFESSIONAL
LIGHTING

LX023893402

LED E14 Filament Tube T20x55mm 230V
210Lm 3W 2500K 925 360° AC Clear
Dimmable

Decorative, Tubular Fila Premium



General		Energy																			
Epel registration no	1297385	Operating voltage	230 V																		
Socket	E14	Volt	220..240 V																		
Bulb shape	T20	Frequency	50..60 Hz																		
Width	20.00 mm	Watt	3 W																		
Depth	20.00 mm	Current type	AC																		
Height	55.00 mm	Power factor	0.8																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	3 W																		
Body material	Glass	Replacement wattage	22 W																		
Lifespan	25000 hours	Lamp efficacy	70.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>28 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	28 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	28 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.007 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LX023893402</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739067172</td></tr><tr><td>Inner carton</td><td>50</td><td>18718739067179</td></tr><tr><td>Outer carton</td><td>200</td><td>28718739067176</td></tr></table>		LX023893402	Quantity pc(s)	EAN	Single package	1	8718739067172	Inner carton	50	18718739067179	Outer carton	200	28718739067176						
LX023893402	Quantity pc(s)			EAN																	
Single package	1			8718739067172																	
Inner carton	50			18718739067179																	
Outer carton	200			28718739067176																	
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	210 lm																				
Color Rendering Index (CRI)	93																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

06-04-2025