



PROFESSIONAL
LIGHTING

LX023893602

LED E14 Filament Tube T20x115mm 230V
320Lm 4W 2500K 925 360° AC Clear
Dimmable

Decorative, Tubular Fila Premium



General		Energy																			
Epel registration no	1424558	Operating voltage	230 V																		
Socket	E14	Volt	220..240 V																		
Bulb shape	T20	Frequency	50..60 Hz																		
Width	20.00 mm	Watt	4 W																		
Depth	20.00 mm	Current type	AC																		
Height	115.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	30 W																		
Lifespan	25000 hours	Lamp efficacy	80.00																		
Switches	15000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>68 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	2	Stick length	68 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	2																				
Stick length	68 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.015 kg																				
Warranty	2 years																				
Light																					
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	320 lm																				
Color Rendering Index (CRI)	90																				
		Ordering details																			
		LX023893602	Quantity pc(s) EAN																		
		Single package	1 8718739068766																		
		Inner carton	50 18718739068763																		
		Outer carton	200 28718739068760																		



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)



07-04-2025