



PROFESSIONAL
LIGHTING

LX023922305

LED E27 Filament Flex AX Tube
T45x130mm 230V 200Lm 4W 2000K 920
360° AC Gold Dimmable

Decorative, Flex AX Tube Premium



General		Energy																			
Eprel registration no	1654813	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	T45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	4 W																		
Depth	45.00 mm	Current type	AC																		
Height	130.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Gold	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	21 W																		
Lifespan	15000 hours	Lamp efficacy	50.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>300 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Axial</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	1	Stick length	300 mm	Stick mounting	Spiral Axial	Colour consistency SDCM	SDCM5	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	1																				
Stick length	300 mm																				
Stick mounting	Spiral Axial																				
Colour consistency SDCM	SDCM5																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.034 kg																				
Warranty	2 years																				
Light		Ordering details																			
Kelvin	2000 K	LX023922305	Quantity pc(s) EAN																		
Colour temp nr	920	Single package	1 8718739070462																		
Stable lumen	200 lm	Inner carton	10 18718739070469																		
Color Rendering Index (CRI)	90	Outer carton	100 28718739070466																		



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

22-07-2025