



PROFESSIONAL  
LIGHTING

## LX023960105

LED E27 Filament Flex DH Rustika  
ST64x140mm 230V 320Lm 5W 2000K 820  
360° AC Gold Dimmable

### Decorative, Flex Double Helix



| General                     |                           | Energy  |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
|-----------------------------|---------------------------|---|------------|----------------|----------------|----------|----------------|-----------|---------------------------|-------------------------|----|----------------|--------------|----------------|---------------------|-------------------------|-------|-------------|----|-----------------------|----|
| Epel registration no        | 1474650                   | Operating voltage   | 230 V      |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Socket                      | E27                       | Volt  | 220..240 V |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Bulb shape                  | ST64                      | Frequency   | 50..60 Hz  |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Width                       | 64.00 mm                  | Watt  | 5 W        |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Depth                       | 64.00 mm                  | Current type  | AC         |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Height                      | 140.00 mm                 | Power factor  | 0.75       |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Finish                      | Clear                     | Energy efficiency class   | G          |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Colour                      | Gold                      | Energy consumption  | 5 W        |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Body material               | Glass                     | Replacement wattage   | 30 W       |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Lifespan                    | 15000 hours               | Lamp efficacy   | 64.00      |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Switches                    | 30000                     | <div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>130 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Double helix</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> |            | Filament LED   | Yes            | LED type | Flex           | Dimm type | Trailing and leading edge | Number of leds / sticks | 2  | Stick length   | 130 mm       | Stick mounting | Spiral Double helix | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED                | Yes                       |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| LED type                    | Flex                      |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Dimm type                   | Trailing and leading edge |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Number of leds / sticks     | 2                         |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Stick length                | 130 mm                    |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Stick mounting              | Spiral Double helix       |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Colour consistency SDCM     | SDCM6                     |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Dim to warm                 | No                        |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Adjustable beam angle       | No                        |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Beam angle                  | 360 °                     |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Dimmable                    | Yes                       |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Degree of protection        | IP20                      |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Net weight                  | 0.043 kg                  |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Warranty                    | 2 years                   |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Light                       |                           | <div>Ordering details</div> <table><tr><td>LX023960105</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739068599</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739068596</td></tr><tr><td>Outer carton</td><td>50</td><td>28718739068593</td></tr></table>   |            | LX023960105    | Quantity pc(s) | EAN      | Single package | 1         | 8718739068599             | Inner carton            | 10 | 18718739068596 | Outer carton | 50             | 28718739068593      |                         |       |             |    |                       |    |
| LX023960105                 | Quantity pc(s)            |   |            | EAN            |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Single package              | 1                         |   |            | 8718739068599  |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Inner carton                | 10                        |   |            | 18718739068596 |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Outer carton                | 50                        |   |            | 28718739068593 |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Kelvin                      | 2000 K                    |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Colour temp nr              | 820                       |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Stable lumen                | 320 lm                    |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |
| Color Rendering Index (CRI) | 82                        |   |            |                |                |          |                |           |                           |                         |    |                |              |                |                     |                         |       |             |    |                       |    |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

23-06-2025