



PROFESSIONAL
LIGHTING

LX023960105

LED E27 Filament Flex DH Rustika
ST64x140mm 230V 320Lm 5W 2000K 820
360° AC Gold Dimmable

Decorative, Flex Double Helix



General		Energy																			
Epel registration no	1474650	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	ST64	Frequency	50..60 Hz																		
Width	64.00 mm	Watt	5 W																		
Depth	64.00 mm	Current type	AC																		
Height	140.00 mm	Power factor	0.75																		
Finish	Clear	Energy efficiency class	G																		
Colour	Gold	Energy consumption	5 W																		
Body material	Glass	Replacement wattage	30 W																		
Lifespan	15000 hours	Lamp efficacy	64.00																		
Switches	30000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>130 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Double helix</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	2	Stick length	130 mm	Stick mounting	Spiral Double helix	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	2																				
Stick length	130 mm																				
Stick mounting	Spiral Double helix																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.043 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LX023960105</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739068599</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739068596</td></tr><tr><td>Outer carton</td><td>50</td><td>28718739068593</td></tr></table>		LX023960105	Quantity pc(s)	EAN	Single package	1	8718739068599	Inner carton	10	18718739068596	Outer carton	50	28718739068593						
LX023960105	Quantity pc(s)			EAN																	
Single package	1			8718739068599																	
Inner carton	10			18718739068596																	
Outer carton	50			28718739068593																	
Kelvin	2000 K																				
Colour temp nr	820																				
Stable lumen	320 lm																				
Color Rendering Index (CRI)	82																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

09-05-2025