



PROFESSIONAL
LIGHTING

LX023960205-1

LED E27 Filament Flex DL Rustika
ST64x143mm 230V 380Lm 5W 2000K 920
360° AC Gold Dimmable

Decorative, Flex Double Loop Helix



General		Energy																			
Epel registration no	2173771	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	ST64	Frequency	50..60 Hz																		
Width	64.00 mm	Watt	5 W																		
Depth	64.00 mm	Current type	AC																		
Height	143.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Gold	Energy consumption	5 W																		
Body material	Glass	Replacement wattage	34 W																		
Lifespan	15000 hours	Lamp efficacy	76.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>130 mm</td></tr><tr><td>Stick mounting</td><td>Double Loop</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	2	Stick length	130 mm	Stick mounting	Double Loop	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	2																				
Stick length	130 mm																				
Stick mounting	Double Loop																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.041 kg																				
Warranty	2 years																				

Light	
Kelvin	2000 K
Colour temp nr	920
Stable lumen	380 lm
Color Rendering Index (CRI)	90

Ordering details		
LX023960205-1	Quantity pc(s)	EAN
Single package	1	8718739077393
Inner carton	10	18718739077390
Outer carton	100	28718739077397



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

29-06-2025