



PROFESSIONAL
LIGHTING

LX023970309

LED E27 Filament Flex TR GLS A60x105mm
230V 210Lm 4W 2200K 922 360° AC Clear
Dimmable

Decorative, Flex GLS Premium



General		Energy																			
Epel registration no	1297080	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	A60	Frequency	50..60 Hz																		
Width	60.00 mm	Watt	4 W																		
Depth	60.00 mm	Current type	AC																		
Height	105.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	22 W																		
Lifespan	15000 hours	Lamp efficacy	52.50																		
Switches	15000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>240 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Transversal</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	1	Stick length	240 mm	Stick mounting	Spiral Transversal	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	1																				
Stick length	240 mm																				
Stick mounting	Spiral Transversal																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.038 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LX023970309</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739067585</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739067582</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739067589</td></tr></table>		LX023970309	Quantity pc(s)	EAN	Single package	1	8718739067585	Inner carton	10	18718739067582	Outer carton	100	28718739067589						
LX023970309	Quantity pc(s)			EAN																	
Single package	1			8718739067585																	
Inner carton	10			18718739067582																	
Outer carton	100			28718739067589																	
Kelvin	2200 K																				
Colour temp nr	922																				
Stable lumen	210 lm																				
Color Rendering Index (CRI)	90																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

29-06-2025