



PROFESSIONAL
LIGHTING

LX024026702

LED Ba15d Filament Pygmy P26x56mm
230V 210Lm 3W 2500K 925 360° AC Clear
Dimmable

Decorative, Pygmy Fila Premium



| General | | Energy | |
|-----------------------------|-------------|-------------------------|---------------------------|
| Epel registration no | 1318866 | Operating voltage | 230 V |
| Socket | Ba15d | Volt | 185..265 V |
| Bulb shape | P26 | Frequency | 50..60 Hz |
| Width | 26.00 mm | Watt | 3 W |
| Depth | 26.00 mm | Current type | AC |
| Height | 56.00 mm | Power factor | 0.85 |
| Finish | Clear | Energy efficiency class | G |
| Colour | Colourless | Energy consumption | 3 W |
| Body material | Glass | Replacement wattage | 22 W |
| Lifespan | 25000 hours | Lamp efficacy | 70.00 |
| Switches | 30000 | LED | |
| Beam angle | 360 ° | Filament LED | Yes |
| Dimmable | Yes | LED type | Ceramic |
| Degree of protection | IP20 | Dimm type | Trailing and leading edge |
| Net weight | 0.010 kg | Number of leds / sticks | 4 |
| Warranty | 2 years | Stick length | 28 mm |
| Light | | Stick mounting | Straight |
| Kelvin | 2500 K | Colour consistency SDCM | SDCM5 |
| Colour temp nr | 925 | Dim to warm | No |
| Stable lumen | 210 lm | Adjustable beam angle | No |
| Color Rendering Index (CRI) | 93 | Ordering details | |
| | | LX024026702 | Quantity pc(s) |
| | | Single package | 1 |
| | | Inner carton | 10 |
| | | Outer carton | 100 |
| | | EAN | |
| | | 8718739067738 | |
| | | 18718739067735 | |
| | | 28718739067732 | |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

04-12-2024