



PROFESSIONAL
LIGHTING

LX024026702

LED Ba15d Filament Pygmy P26x56mm
230V 210Lm 3W 2500K 925 360° AC Clear
Dimmable

Decorative, Pygmy Fila Premium



| General | |
|----------------------|-------------|
| Epel registration no | 1318866 |
| Socket | Ba15d |
| Bulb shape | P26 |
| Width | 26.00 mm |
| Depth | 26.00 mm |
| Height | 56.00 mm |
| Finish | Clear |
| Colour | Colourless |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 30000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.010 kg |
| Warranty | 2 years |

Light

| | |
|-----------------------------|--------|
| Kelvin | 2500 K |
| Colour temp nr | 925 |
| Stable lumen | 210 lm |
| Color Rendering Index (CRI) | 93 |

| Energy | | |
|-------------------------|------------|--|
| Operating voltage | 230 V | |
| Volt | 185..265 V | |
| Frequency | 50..60 Hz | |
| Watt | 3 W | |
| Current type | AC | |
| Power factor | 0.85 | |
| Energy efficiency class | G | |
| Energy consumption | 3 W | |
| Replacement wattage | 22 W | |
| Lamp efficacy | 70.00 | |

LED

| | | |
|-------------------------|---------------------------|--|
| Filament LED | Yes | |
| LED type | Ceramic | |
| Dimm type | Trailing and leading edge | |
| Number of leds / sticks | 4 | |
| Stick length | 28 mm | |
| Stick mounting | Straight | |
| Colour consistency SDCM | SDCM5 | |
| Dim to warm | No | |
| Adjustable beam angle | No | |

Ordering details

| | | |
|----------------|----------------|----------------|
| LX024026702 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739067738 |
| Inner carton | 10 | 18718739067735 |
| Outer carton | 100 | 28718739067732 |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

19-04-2025