PROFESSIONAL LIGHTING

## LX024040301

LED Ba15d Filament Candle C35x100mm
230V 320Lm 4W 2500K 925 360° AC
Frosted Dimmable

**Decorative, Candle Premium**

| General | |
|---|---|
| Eprel registration no | 1405998 |
| Socket | Ba15d |
| Bulb shape | C35 |
| Width | 35.00 mm |
| Depth | 35.00 mm |
| Height | 100.00 mm |
| Finish | Frosted |
| Colour | Colourless |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.017 kg |
| Warranty | 2 years |

| Light | |
|---|---|
| Kelvin | 2500 K |
| Colour temp nr | 925 |
| Stable lumen | 320 lm |
| Color Rendering Index (CRI) | 93 |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 4 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | G |
| Energy consumption | 4 W |
| Lamp efficacy | 80.00 |

| LED | |
|---|---|
| Filament LED | Yes |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 4 |
| Stick length | 38 mm |
| Stick mounting | Twisted |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|---|---|---|
| LX024040301 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739068650 |
| Inner carton | 10 | 18718739068657 |
| Outer carton | 100 | 28718739068654 |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal