



PROFESSIONAL
LIGHTING

LX024070501

LED Ba22d Filament GLS A60x105mm 230V
500Lm 5.5W 2500K 925 360° AC Frosted
Dimmable

Decorative, General Ba22d Premium



General		Energy	
Epel registration no	1586952	Operating voltage	230 V
Socket	Ba22d	Volt	220..240 V
Bulb shape	A60	Frequency	50..60 Hz
Width	60.00 mm	Watt	5.5 W
Depth	60.00 mm	Current type	AC
Height	105.00 mm	Power factor	0.9
Finish	Frosted	Energy efficiency class	F
Colour	Colourless	Energy consumption	6 W
Body material	Glass	Replacement wattage	42 W
Lifespan	25000 hours	Lamp efficacy	90.91
Switches	50000	LED	
Beam angle	360 °	Filament LED	Yes
Dimmable	Yes	LED type	Ceramic
Degree of protection	IP20	Dimm type	Trailing and leading edge
Net weight	0.030 kg	Number of leds / sticks	6
Warranty	2 years	Stick length	38 mm
Light		Stick mounting	Straight
Kelvin	2500 K	Colour consistency SDCM	SDCM5
Colour temp nr	925	Dim to warm	No
Stable lumen	500 lm	Adjustable beam angle	No
Color Rendering Index (CRI)	93	Ordering details	
		LX024070501	Quantity pc(s) EAN
		Single package	1 8718739070028
		Inner carton	10 18718739070025
		Outer carton	100 28718739070022



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

28-06-2025