PROFESSIONAL LIGHTING

LX024070501

LED Ba22d Filament GLS A60x105mm 230V 500Lm 5.5W 2500K 925 360° AC Frosted Dimmable

Decorative, General Ba22d Premium







General	
Eprel registration no	1586952
Socket	Ba22d
Bulb shape	A60
Width	60.00 mm
Depth	60.00 mm
Height	105.00 mm
Finish	Frosted
Colour	Colourless
Body material	Glass
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.030 kg
Warranty	2 years

Light	
CRI	93
Kelvin	2500 K
Colour temp nr	925
Stable lumen	500 lm

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	5.5 W
Current type	AC
Power factor	0.9
Energy efficiency class	F
Energy consumption	6 W
Lamp efficacy	90.91

LED	
Filament LED	Yes
LED type	Ceramic
Dimm type	Trailing and leading edge
Number of leds / sticks	6
Stick length	38 mm
Stick mounting	Straight
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Ordering details		
LX024070501	Quantity pc(s)	EAN
Single package	1	8718739070028
Inner carton	10	18718739070025
Outer carton	100	28718739070022

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal