PROFESSIONAL LIGHTING

## LX025501619

LED S14d Filament T30x500mm 230V 240Lm 4W 2200K 922 360° AC Frosted Dimmable

**Household, S14d Filament Premium**



| General | |
|---|---|
| Eprel registration no | 2271189 |
| Socket | S14d |
| Bulb shape | T30 |
| Width | 30.00 mm |
| Depth | 47.00 mm |
| Height | 500.00 mm |
| Finish | Frosted |
| Colour | Colourless |
| Body material | Glass |
| Lifespan | 15000 hours |
| Switches | 25000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.115 kg |
| Warranty | 2 years |

| Light | |
|---|---|
| CRI | 95 |
| Kelvin | 2200 K |
| Colour temp nr | 922 |
| Stable lumen | 240 lm |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 4 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | G |
| Energy consumption | 4 W |
| Lamp efficacy | 60.00 |

| LED | |
|---|---|
| Filament LED | Yes |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 1 |
| Stick length | 460 mm |
| Stick mounting | Straight |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|---|---|---|
| LX025501619 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739072633 |
| Outer carton | 50 | 28718739072637 |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal