
PROFESSIONAL LIGHTING

## LX142404922

LED E14 Filament Ball G45x75mm 24V 270Lm 4W-AC 3W-DC 2200K 922 360° AC/DC Clear Non-Dimmable

**Marine & Industry, Ball 24V Filament Premium**








| General | |
|---|---|
| Eprel registration no | 1597643 |
| Socket | E14 |
| Bulb shape | G45 |
| Width | 45.00 mm |
| Depth | 45.00 mm |
| Height | 75.00 mm |
| Finish | Clear |
| Colour | Colourless |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 30000 |
| Beam angle | 360 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.014 kg |
| Warranty | 2 years |

| Light | |
|---|---|
| CRI | 93 |
| Kelvin | 2200 K |
| Colour temp nr | 922 |
| Stable lumen | 270 lm |

| Energy | |
|---|---|
| Operating voltage | 24 V |
| Volt | 24 V |
| Frequency | 50..60 Hz |
| Watt | 4 W |
| Current type | AC/DC |
| Power factor | 0.7 |
| Energy efficiency class | G |
| Energy consumption | 4 W |
| Lamp efficacy | 67.50 |

| LED | |
|---|---|
| Filament LED | Yes |
| LED type | Ceramic |
| Dimm type | Non-Dim |
| Number of leds / sticks | 4 |
| Stick length | 38 mm |
| Stick mounting | Vertical |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|---|---|---|
| LX142404922 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739070813 |
| Inner carton | 10 | 18718739070810 |
| Outer carton | 100 | 28718739070817 |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal